

## SYSTEM MATERIAL USAGE

Series	Coil Size	Panel Size	Material Usage (Diff)	Approx. Ft/Min	Panel Size Variable	Max. Material Thickness
A 1000 (1 1/2" Snap-Lock System)	24"	20"	4"	30'	12" - 20"	24 Gauge
A 1100 (1 1/4" Integral Snap-Lock System)	20"	16"	4"	30'	16" Fixed	24 Gauge
A 1101 (1" Integral Snap-Lock System)	20"	16"	4"	30'	16" Fixed	24 Gauge
A 1300 (1 1/2" Mechanically Seamed System)	24"	20"	4"	30'	12" - 24"	22 Gauge
A 1301 (1" Mechanically Seamed System)	24"	21"	3"	30'	13" - 21"	22 Gauge
A 1500 (1 1/2" Integral Snap-Lock System)	24"	20"	4"	30'	12" - 24"	22 Gauge
C 1300 (1 1/2" Curved Mechanically Seamed System)	24"	20"	4"	30'	12" - 24"	24 Gauge
C 1301 (1" Curved Mechanically Seamed System)	24"	21"	3"	30'	13" - 21"	24 Gauge
C 2400 (2" Curved Mechanically Seamed System)	24"	18"	6"	40'	12" - 24"	22 Gauge
S 2000 (1 3/4" Integral Snap-Lock System)	24"	18"	6"	40'	12" - 18"	22 Gauge
S 2400 (2" Mechanically Seamed System)	24"	18"	6"	70'	12" - 24"	22 Gauge
S 2500 (2" Mechanically Seamed System)*	22"	16"	6"	50'	12" - 18"	22 Gauge
S 3000 (3" T-Seam Mechanically Seamed System)*	26"	20"	6"	40'	12", 14", 16", 18" 20"	20 Gauge
A 4000 (1 1/2" Flush Wall Panel)	24"	18"	6"	30'	12" - 24"	22 Gauge
B 4000 (1" Flush Soffit Wall Panel)	24"	20"	4"	30'	12" - 24"	22 Gauge

\*Sun tested version available, see Englert for details.

*This calculator is for estimation purposes only. For precise information on calculating coil purchases, contact: The Englert Customer Value Center at 1-800-ENGLERT (1-800-364-5378) for more information and assistance.*